



**COLOR SWATCHES**  
cut from actual size

White Glossy 3x6" | CORE36WHG  
White Glossy 4x16" | CORE416WHG

White Matte 3x6" | CORE36WHM  
White Matte 4x16" | CORE416WHM

Grey Glossy 3x6" | CORE36GRG  
Grey Glossy 4x16" | CORE416GRG

Grey Matte 3x6" | CORE36GRM  
Grey Matte 4x16" | CORE416GRM



*Staples are necessary ingredients that you just need to have on hand to be able to do the task at hand. These basics are the bread and butter of any task we do in a given field. Even basic staples can be exquisitely crafted and designed though.*

*Enter, Core Collection - our two most popular subway formats offered in universally applicable white and light grey in both glossy and matte finishes. With this concise arsenal there are limitless possibilities for any style of project.*

*Don't settle for bargain basics, demand the best from even the simplest products in your project - that's the Core of good design principles.*

## INSTALLATION & MAINTENANCE

- ◆ Ceramic wall tile is suitable for all interior wall or ceiling applications including wet areas. Not suitable for demanding environments such as steam showers
- ◆ All products should be inspected prior to installation for any defects or unacceptable color/shade variation. Claims will not be accepted after installation
- ◆ Proper substrates, preparation and installation materials are required for a successful installation. For reference please see the TCNA 09300 Tile Handbook
- ◆ Non sanded grouts are recommended for high gloss wall tiles
- ◆ Ensure all grout haze is buffed off before 48 hours have elapsed after installation
- ◆ Glazed tile should not be treated with a sealer for any reason
- ◆ To clean glazed ceramic wall tile, use a damp sponge with warm water. For heavy cleaning, use a non abrasive cleaner with a damp sponge
- ◆ Further warranty, best practices, care and maintenance details can be found on our website




Grey Glossy

## TECHNICAL SPECIFICATIONS

Technical Characteristics	ASTM Test Result	ASTM/ANSI Test Method
Water Absorption %	≥10%	A 187.1
Dimensionality (flatness, warpage, straightness, etc.)	premium grade conformance	A 187.1 ISO 10545-2
Thermal Shock & Cracking Resistance	Pass	A 187.1 ISO 10545-9/11
Resistance to Stains, chemicals acids, etc.	Pass	C650 & C1378 ISO 10545-13/14

## PACKAGING

Size	PC/CTN	Sqft/ctn (Sqm/ctn)	Carton/Pallet	Sqft/plt (Sqm/plt)	Lbs/ctn (Kgs/ctn)	Lbs/plt (Kgs/plt)
3x6" (76x152)	100	12.43 (1.16)	54	671.35 (62.37)	34.17 (15.50)	1,845.18 (837.00)
4x16" (100x402)	25	10.76 (1.00)	84	904.26 (84.00)	34.17 (14.50)	2,870.00 (1,302.00)



V1

Minimal Variation

### WHITE Glossy



4x16" | CORE416WHG



3x6" | CORE36WHG

### WHITE Matte



4x16" | CORE416WHM



3x6" | CORE36WHM

### GREY Glossy




4x16" | CORE416GRG




3x6" | CORE36GRG

### GREY Matte



4x16" | CORE416GRM



3x6" | CORE36GRM



Pencil Bullnose  
1/3 x 8"  
8x202mm



Quarter Round  
1/2 x 8"  
8x202mm

\*All trims feature glazed edges (Long) for use as edge trim if desired. Pencil Bullnose and Quarter Round are universal trims and will not feature Core labeling. For more information on Bellavita Trims and uses, please visit our website.

