

COLOR SWATCHES
cut from actual size

Flat

Bevel

Mist

Stretch

Wave

Swoosh

Billet



There's an undeniable allure when something is distilled to its primal essence. When all the dross is removed, you are left with a pure Element that cannot be refined further.

It is with this deceptively complex goal in mind that became our Elements collection.

Seven primal ceramic forms are offered in our most brilliant white glaze without further embellishment.

By pairing our new large-scale 8x24" format, with this glaze and strong forms we feel that the perfect canvas is created for any design language.

INSTALLATION & MAINTENANCE

- ◆ Ceramic wall tile is suitable for all interior wall or ceiling applications including wet areas. Not suitable for demanding environments such as steam showers
- ◆ All products should be inspected prior to installation for any defects or unacceptable color/shade variation. Claims will not be accepted after installation
- ◆ Proper substrates, preparation and installation materials are required for a successful installation. For reference please see the TCNA 09300 Tile Handbook
- ◆ Non sanded grouts are recommended for high gloss wall tiles
- ◆ Ensure all grout haze is buffed off before 48 hours have elapsed after installation
- ◆ Glazed tile should not be treated with a sealer for any reason
- ◆ To clean glazed ceramic wall tile, use a damp sponge with warm water. For heavy cleaning, use a non abrasive cleaner with a damp sponge
- ◆ Further warranty, best practices, care and maintenance details can be found on our website




TECHNICAL SPECIFICATIONS

Technical Characteristics	ASTM Test Result	ASTM/ANSI Test Method
Water Absorption %	≥10%	A 187.1
Dimensionality (flatness, warpage, straightness, etc.)	premium grade conformance	A 187.1 ISO 10545-2
Thermal Shock & Cracking Resistance	Pass	A 187.1 ISO 10545- 9/11
Resistance to Stains, chemicals acids, etc.	Pass	C650 & C1378 ISO 10545- 13/14

PACKAGING

Size	PC/CTN	Sqft/ctn (Sqm/ctn)	Carton/Pallet	Sqft/plt (Sqm/plt)	Lbs/ctn (Kgs/ctn)	Lbs/plt (Kgs/plt)
flat & mist 8x24" (200x300)	10	12.92 (1.20)	64	826.88 (76.82)	48.50 (22.00)	1,358.05 (616.00)
all others 8x24" (200x300)	9	11.63 (1.08)	64	744.32 (69.15)	48.50 (22.00)	1,358.05 (616.00)



V1

Minimal Variation

